

MONO POSTS

DESIGNED AND MANUFACTURED TO COMPLY WITH CAN/CGSB-7.2-94 (CCMC LISTING #13250-L)

Manufacturing Specifications

Finished with corrosion resistant powder coating. One year limited warranty.

Model: 3 in. O.D., 11 Gauge Std: 3 in. O.D. Tube. End Plate: 4 1/4 in. x 7 1/2 in. x 1/4 in. - "M" or "H" Series Adj./Swivel End Plate: 4 in. x 6 in. x 1/4 in.

Model #	Adjustment Range	UPC	Allowable Load	Weight
CA-200	6 ft. 0 in. - 6 ft. 4 in. (1828.8 mm - 1930.4 mm)	7-16733-31256-2	8,742 lbs. (38.9 kN)	30 lbs.
CA-201	6 ft. 3 in. - 6 ft. 7 in. (1905 mm - 2006.6 mm)	7-16733-31264-7	8,742 lbs. (38.9 kN)	31 lbs.
CA-202	6 ft. 6 in. - 6 ft. 10 in. (1981.2 mm - 2082.8 mm)	7-16733-31265-4	8,742 lbs. (38.9 kN)	32 lbs.
CA-203	6 ft. 9 in. - 7 ft. 1 in. (2057.4 mm - 2159 mm)	7-16733-31253-1	8,742 lbs. (38.9 kN)	33 lbs.
CA-204	7 ft. 0 in. - 7 ft. 4 in. (2133.6 mm - 2235.2 mm)	7-16733-31254-8	8,742 lbs. (38.9 kN)	34 lbs.
CA-205	7 ft. 3 in. - 7 ft. 7 in. (2209.8 mm - 2311.4 mm)	7-16733-31255-5	8,742 lbs. (38.9 kN)	35 lbs.
CA-206	7 ft. 6 in. - 7 ft. 10 in. (2286 mm - 2387.6 mm)	7-16733-31249-4	8,742 lbs. (38.9 kN)	36 lbs.
CA-207	7 ft. 9 in. - 8 ft. 1 in. (2362.2 mm - 2463.8 mm)	7-16733-31257-9	8,742 lbs. (38.9 kN)	37 lbs.
CA-208	8 ft. 0 in. - 8 ft. 4 in. (2438.4 mm - 2540 mm)	7-16733-31258-6	8,742 lbs. (38.9 kN)	37 lbs.
CA-209	8 ft. 3 in. - 8 ft. 7 in. (2514.6 mm - 2616.2 mm)	7-16733-31259-3	8,742 lbs. (38.9 kN)	38 lbs.
CA-210	8 ft. 6 in. - 8 ft. 10 in. (2590.8 mm - 2692.4 mm)	7-16733-31250-0	8,742 lbs. (38.9 kN)	39 lbs.
CA-211	8 ft. 9 in. - 9 ft. 1 in. (2667 mm - 2768.6 mm)	7-16733-31251-7	8,742 lbs. (38.9 kN)	40 lbs.
CA-212	9 ft. 0 in. - 9 ft. 4 in. (2743.2 mm - 2844.8 mm)	7-16733-31252-4	8,742 lbs. (38.9 kN)	41 lbs.
CA-213	9 ft. 3 in. - 9 ft. 7 in. (2819.4 mm - 2921 mm)	7-16733-31260-9	8,742 lbs. (38.9 kN)	42 lbs.
CA-214	9 ft. 6 in. - 9 ft. 10 in. (2895.6 mm - 2997.2 mm)	7-16733-31261-6	8,742 lbs. (38.9 kN)	43 lbs.
CA-215	9 ft. 9 in. - 10 ft. 1 in. (2971.8 mm - 3073.4 mm)	7-16733-31262-3	8,742 lbs. (38.9 kN)	44 lbs.

MONO POSTS

DESIGNED AND MANUFACTURED TO COMPLY WITH CAN/CGSB-7.2-94 (CCMC LISTING #13250-L)

Manufacturing Specifications

Finished with corrosion resistant powder coating. One year limited warranty.

Model: 3 1/2 in. O.D., 11 Gauge Std: 3 1/2 in. O.D. Tube. End Plate: 4 1/4 in. x 7 1/2 in. x 1/4 in. - "M" or "H" Series Adj./Swivel End Plate: 4 in. x 6 in. x 1/4 in.

Model #	Adjustment Range	UPC	Allowable Load	Weight
CA-300	6 ft. 0 in. - 6 ft. 4 in. (1828.8 mm - 1930.4 mm)	7-16733-31289-0	15,717 lbs. (69.9 kN)	34 lbs.
CA-301	6 ft. 3 in. - 6 ft. 7 in. (1905 mm - 2006.6 mm)	7-16733-31290-6	15,717 lbs. (69.9 kN)	35 lbs.
CA-302	6 ft. 6 in. - 6 ft. 10 in. (1981.2 mm - 2082.8 mm)	7-16733-31291-3	15,717 lbs. (69.9 kN)	36 lbs.
CA-303	6 ft. 9 in. - 7 ft. 1 in. (2057.4 mm - 2159 mm)	7-16733-31292-0	15,717 lbs. (69.9 kN)	38 lbs.
CA-304	7 ft. 0 in. - 7 ft. 4 in. (2133.6 mm - 2235.2 mm)	7-16733-31263-0	15,717 lbs. (69.9 kN)	62 lbs.
CA-305	7 ft. 3 in. - 7 ft. 7 in. (2209.8 mm - 2311.4 mm)	7-16733-31293-7	15,717 lbs. (69.9 kN)	39 lbs.
CA-306	7 ft. 6 in. - 7 ft. 10 in. (2286 mm - 2387.6 mm)	7-16733-31266-1	15,717 lbs. (69.9 kN)	40 lbs.
CA-307	7 ft. 9 in. - 8 ft. 1 in. (2362.2 mm - 2463.8 mm)	7-16733-31267-8	15,717 lbs. (69.9 kN)	41 lbs.
CA-308	8 ft. 0 in. - 8 ft. 4 in. (2438.4 mm - 2540 mm)	7-16733-31268-5	15,717 lbs. (69.9 kN)	42 lbs.
CA-309	8 ft. 3 in. - 8 ft. 7 in. (2514.6 mm - 2616.2 mm)	7-16733-31294-4	15,717 lbs. (69.9 kN)	43 lbs.
CA-310	8 ft. 6 in. - 8 ft. 10 in. (2590.8 mm - 2692.4 mm)	7-16733-31295-1	15,717 lbs. (69.9 kN)	45 lbs.
CA-311	8 ft. 9 in. - 9 ft. 1 in. (2667 mm - 2768.6 mm)	7-16733-31269-2	15,717 lbs. (69.9 kN)	46 lbs.
CA-312	9 ft. 0 in. - 9 ft. 4 in. (2743.2 mm - 2844.8 mm)	7-16733-31296-8	15,717 lbs. (69.9 kN)	47 lbs.
CA-313	9 ft. 3 in. - 9 ft. 7 in. (2819.4 mm - 2921 mm)	7-16733-31297-5	15,717 lbs. (69.9 kN)	48 lbs.
CA-314	9 ft. 6 in. - 9 ft. 10 in. (2895.6 mm - 2997.2 mm)	7-16733-31298-2	15,717 lbs. (69.9 kN)	49 lbs.
CA-315	9 ft. 9 in. - 10 ft. 1 in. (2971.8 mm - 3073.4 mm)	7-16733-31270-8	15,717 lbs. (69.9 kN)	50 lbs.
CA-316	10 ft. 0 in. - 10 ft. 4 in. (3048 mm - 3149.6 mm)	7-16733-31271-5	15,717 lbs. (69.9 kN)	51 lbs.

© The Akron Products Company - CA-FLOOR-MONO 11220



The Akron Products Company

10721 South Water Street Ext. • Meadville, PA 16335
Phone: 330-576-1750 • Fax: 330-576-1755
e-mail us: info@akronproducts.com

MONO POSTS (cont.)

DESIGNED AND MANUFACTURED TO COMPLY WITH CAN/CGSB-7.2-94 (CCMC LISTING #13250-L)

Manufacturing Specifications

Finished with corrosion resistant powder coating. One year limited warranty.

Model: Schedule 40 Series

Std: 3½ in. O.D. Tube. End Plate: 4 ¼ in. x 7 ½ in. x ¼ in. - Adj./Swivel End Plate: 4 in. x 6 in. x ¼ in.

Model #	Adjustment Range	UPC	Allowable Load	Weight
CA-300-40	6 ft. 0 in. - 6 ft. 4 in. (1828.8 mm x 1930.4 mm)	7-16733-31272-2	18,507 lbs. / 82.3 kN	54 lbs.
CA-301-40	6 ft. 3 in. - 6 ft. 7 in. (1905.0mm x 2006.6 mm)	7-16733-31273-9	18,507 lbs. / 82.3 kN	56 lbs.
CA-302-40	6 ft. 6 in. - 6 ft. 10 in. (1981.2mm x 2082.8mm)	7-16733-31274-6	18,507 lbs. / 82.3 kN	58 lbs.
CA-303-40	6 ft. 9 in. - 7 ft. 1 in. (2057mm x 2159.0mm)	7-16733-31275-3	18,507 lbs. / 82.3 kN	60 lbs.
CA-304-40	7 ft. 0 in. - 7 ft. 4 in. (2133.6 mm x 3987.8mm)	7-16733-31276-0	18,507 lbs. / 82.3 kN	62 lbs.
CA-305-40	7 ft. 3 in. - 7 ft. 7 in. (2209.8mm x 2387.6mm)	7-16733-31277-7	18,507 lbs. / 82.3 kN	64 lbs.
CA-306-40	7 ft. 6 in. - 7 ft. 10 in. (2286.0mm x 2387.6mm)	7-16733-31278-4	18,507 lbs. / 82.3 kN	66 lbs.
CA-307-40	7 ft. 9 in. - 8 ft. 1 in. (2362.2mm x 2463.8mm)	7-16733-31279-1	18,507 lbs. / 82.3 kN	67 lbs.
CA-308-40	8 ft. 0 in. - 8 ft. 4 in. (2438.4mm x 2540.0mm)	7-16733-31280-7	18,507 lbs. / 82.3 kN	69 lbs.
CA-309-40	8 ft. 3 in. - 8 ft. 7 in. (2514.6mm x 2616.2mm)	7-16733-31281-4	18,507 lbs. / 82.3 kN	71 lbs.
CA-310-40	8 ft. 6 in. - 8 ft. 10 in. (2590.8mm x 2692.4mm)	7-16733-31282-1	18,507 lbs. / 82.3 kN	73 lbs.
CA-311-40	8 ft. 9 in. - 9 ft. 1 in. (2667.0mm x 2768.6mm)	7-16733-31283-8	18,507 lbs. / 82.3 kN	75 lbs.
CA-312-40	9 ft. 0 in. - 9 ft. 4 in. (2743.2mm x 2844.8mm)	7-16733-31284-5	18,507 lbs. / 82.3 kN	77 lbs.
CA-313-40	9 ft. 3 in. - 9 ft. 7 in. (2819.4mm x 2921.0mm)	7-16733-31285-2	18,507 lbs. / 82.3 kN	79 lbs.
CA-314-40	9 ft. 6 in. - 9 ft. 10 in. (2895.6mm x 2997.2mm)	7-16733-31286-9	18,507 lbs. / 82.3 kN	81 lbs.
CA-315-40	9 ft. 9 in. - 10 ft. 1 in. (2971.8mm x 3073.4mm)	7-16733-31287-6	18,507 lbs. / 82.3 kN	83 lbs.
CA-316-40	10 ft. 0 in. - 10 ft. 4 in. (3048.0mm x 3149.6mm)	7-16733-31288-3	18,507 lbs. / 82.3 kN	85 lbs.

TAPCO FLOOR JACKS

THESE PRODUCTS MEET THE FOLLOWING STANDARD:
CAN/CGSB-7.2-94, ADJUSTABLE STEEL COLUMNS.CCMC REPORT #13269-L

Model #	Adjustment Range	UPC	Allowable Load	Ctn. Weight
CA-108	6 ft. 2 in. - 9 ft. 0 in. (1879.6 mm - 2743.2 mm)	7-16733-31108-4	8,655 lbs. (38.5 kN)	37 lbs.
CA-84	4 ft. 8 in. - 8 ft. 4 in. (1422.4 mm - 2540 mm)	7-16733-13841-4	8,280 lbs. (36.8 kN)	31 lbs.
CA-2	2 ft. 10 in. - 4 ft. 7 in. (863.6 mm - 1397 mm)	7-16733-13021-0	13,002 lbs. (57.8 kN)	20 lbs.
CA-3	1 ft. 7 in. - 3 ft. 0 in. (482.6 mm - 914.4 mm)	7-16733-13031-9	14,746 lbs. (65.6 kN)	15 lbs.

2½ in. O.D. Lower, 2½ in. O.D. Upper; ¼ in. x 4 in. x 6 in. Plates



TAPCO AREA WALLS

Made of 22 Gauge Galvanized Steel • Deep Corrugations for Extra Strength • Top Fully Rolled for Rigidity and Safety • Wide Pre-Punched Flat Mounting Flanges

Model	Height	Style	Bundle Qty.	Weight
12R	12" (304.8mm)	Round	5	31 lbs.
15R	15" (381.0mm)	Round	5	43 lbs.
18R	18" (457.2mm)	Round	5	45 lbs.
24R	24" (609.6mm)	Round	5	59 lbs.
30R	30" (762.0mm)	Round	5	72 lbs.
36R	36" (914.4mm)	Round	5	81 lbs.
48R	48" (1,219.2mm)	Round	5	125 lbs.

Model	Height	Style	Bundle Qty.	Weight
12 Vent	12" (304.8mm)		10	35 lbs.

Model	Height	Style	Bundle Qty.	Weight
12S	12" (304.8mm)	Square	5	33 lbs.
15S	15" (381.0mm)	Square	5	38 lbs.
18S	18" (457.2mm)	Square	5	41 lbs.
24S	24" (609.6mm)	Square	5	63 lbs.
30S	30" (762.0mm)	Square	5	74 lbs.
36S	36" (914.4mm)	Square	5	95 lbs.

© The Akron Products Company - CA-FLOOR-MONO 112210



The Akron Products Company

10721 South Water Street Ext. • Meadville, PA 16335
Phone: 330-576-1750 • Fax: 330-576-1755
e-mail us: info@akronproducts.com